

Data version: 20111008

Group B: '091					'092			
RPM	Load	Idle Stabili.	Idle Stabilization	TIME	RPM	Load	Idle Stabili.	Idle Stabili.
/min	%	°KW	°KW	STAMP	/min	%	°KW	°KW
1200	43.1	8.5	8.5	0.44	1280	42.0	11.5	11.0
1280	47.1	12.5	11.5	0.96	1440	47.5	24.5	22.5
1520	50.2	28.5	27.0	1.47	1560	38.0	32.0	33.5
1600	47.1	33.0	32.5	1.97	1760	47.5	39.5	37.5
1800	49.4	43.5	42.5	2.47	1840	41.2	46.0	46.5
1840	43.5	46.0	47.0	2.99	1680	22.0	38.5	45.5
1680	41.2	33.0	34.0	3.49	1680	39.2	33.5	33.5
1680	42.7	33.5	34.0	3.99	1720	43.9	34.5	33.0
1720	45.5	35.5	35.0	4.49	1720	42.4	36.0	35.5
1720	44.7	36.5	36.0	4.99	1760	40.0	37.5	37.5
1760	43.9	38.0	38.0	5.49	1760	43.1	39.0	38.0
1800	45.5	39.5	39.0	5.99	1800	42.7	41.5	41.0
1840	43.9	42.0	42.0	6.49	1840	42.7	43.0	42.5
1840	44.3	43.5	43.5	6.99	1880	42.4	44.5	44.0
1880	44.3	45.0	45.0	7.49	1880	43.9	46.5	45.5
1920	44.7	47.0	46.5	8.01	1920	41.6	48.5	48.0
1960	45.1	49.0	48.5	8.52	1960	42.0	50.0	49.5
1960	45.9	50.5	50.0	9.02	1960	45.1	51.0	49.5
1960	45.5	51.0	50.5	9.52	2000	44.7	52.0	51.0
2000	48.6	52.0	50.5	10.02	2000	46.7	52.0	50.5
2000	49.4	52.0	50.5	10.52	2000	47.1	52.0	51.0
2000	50.2	52.0	51.0	11.03	2040	48.2	52.0	51.0
2040	52.5	52.0	50.5	11.54	2040	48.2	52.0	51.5
2040	53.7	52.0	50.5	12.06	2040	49.0	52.0	51.5
2080	54.9	52.0	50.5	12.57	2080	51.0	52.0	51.0
2120	55.7	52.0	50.5	13.07	2120	51.4	52.0	51.5
2120	56.5	52.0	51.0	13.57	2240	53.3	52.0	51.0
2560	42.7	49.5	50.0	14.07	2840	39.6	47.0	47.5
2880	43.9	46.0	46.0	14.57	2960	40.0	45.0	45.5
3000	47.1	44.5	43.5	15.06	3080	38.4	43.0	44.0
3120	40.8	42.5	43.5	15.56	3200	38.0	40.5	41.5
3240	42.0	40.0	40.0	16.03	3320	40.4	38.0	38.0
3360	43.1	37.5	37.0	16.48	3480	40.4	35.5	36.0
3520	44.3	34.5	34.0	16.96	3640	43.1	34.0	33.0
3680	50.2	33.5	31.0	17.47	3800	41.6	33.0	32.5
3840	44.7	33.0	33.0	17.99	3960	44.7	32.0	30.5
4000	46.7	32.0	31.0	18.51	4120	42.7	30.5	30.0
4160	45.1	29.5	29.5	19.02	4280	40.0	28.5	29.0
4320	45.9	27.5	27.0	19.54	4440	41.6	26.0	26.0
4480	46.7	25.5	24.5	20.05	4600	45.9	28.0	26.5
4640	55.7	30.5	26.5	20.55	4720	45.5	35.5	34.0
4800	49.8	36.5	35.5	21.07	4880	42.0	35.0	35.0
4960	40.0	34.5	36.0	21.58	5040	43.1	33.5	33.0
5120	45.9	33.5	33.0	22.08	5200	42.0	33.0	33.0
5240	43.1	32.5	33.0	22.59	5360	41.6	32.5	32.5
5400	44.7	32.0	32.0	23.09	5520	42.7	31.5	31.0

5560 44.3	31.0	31.0	23.60	5320 28.2	33.5	38.0
5240 24.7	25.0	35.0	24.11	5160 43.1	23.0	22.0
5160 52.5	23.0	19.5	24.60	5080 43.5	23.0	22.0
5080 49.0	23.0	20.5	25.12	5000 41.6	23.0	22.5
4960 49.0	23.0	20.5	25.62	4880 41.6	23.0	23.0
4840 44.7	23.0	22.5	26.13	4920 38.8	4.0	4.5
5080 45.1	15.5	10.5	26.63	5120 42.0	10.5	10.0
5120 45.9	10.5	9.5	27.12	5160 42.4	10.5	10.0
5200 41.6	12.5	13.5	27.64	5240 40.4	14.0	12.5
5320 84.7	25.5	16.5	28.13	5440 39.6	32.0	33.0
5520 44.3	31.5	32.0	28.65	5600 41.2	29.5	30.0
5680 41.6	28.5	29.5	29.17	5760 40.4	27.0	27.0
5800 44.3	26.0	26.0	29.69	5880 39.2	23.5	24.0
5960 43.5	23.0	23.0	30.20	6040 41.6	22.0	21.5
6080 44.3	22.0	21.5	30.68	6160 42.0	22.0	21.5
6200 44.3	22.0	21.5	31.16	6320 42.0	22.0	21.5
6360 43.9	22.0	22.0	31.68	6200 41.6	22.0	22.0
6120 33.3	38.0	37.0	32.18	6080 40.0	23.0	22.5
6000 45.9	23.0	22.0	32.69	5920 40.8	23.0	22.5
5880 43.9	23.0	22.5	33.20	5520 41.6	23.0	22.0
5080 44.7	22.0	21.5	33.71	4280 40.0	22.0	22.0
3920 43.9	22.0	22.0	34.22	3880 41.6	22.0	21.5
3880 43.9	22.0	22.0	34.71	3840 39.6	22.0	22.0
3800 43.9	22.0	22.0	35.21	3520 41.6	22.0	21.5
3280 44.7	22.0	21.5	35.71	2760 41.6	22.0	21.5
2680 44.7	22.0	21.5	36.21	2600 40.8	22.0	21.5
2560 44.7	22.0	21.5	36.71	2520 41.6	22.0	21.5
2520 43.5	22.0	22.0	37.21	2480 40.0	22.0	22.0
2480 44.3	22.0	22.0	37.71	2440 40.4	22.0	21.5
2440 43.1	22.0	22.0	38.21	2400 40.0	22.0	22.0
2400 43.1	22.0	22.0	38.71	2360 42.0	22.0	21.5
2360 44.3	22.0	21.5	39.23	2320 40.4	22.0	22.0
2320 42.7	22.0	22.0	39.74	2280 40.0	22.0	22.0
2280 42.7	22.0	22.0	40.24	2240 39.6	22.0	22.0
2240 41.2	22.0	22.5	40.74	2200 38.8	22.0	22.5
2200 40.0	22.0	22.5	41.24	2160 39.2	22.0	22.0

Wednesda
4D0 907 560 BF

1 November
4.2L V8/5V

2017 20:20:00:1 VCDS Version: Beta 11.6.0
G 0020

Group C:		Group A: '093		
zation		Idle Stabili. Idle Stabili.		
TIME		TIME		
STAMP	Marker	STAMP	°KW	°KW
0.11		0.28	-3.0	-2.0
0.61		0.79	-3.0	-2.0
1.13		1.30	-3.0	-2.0
1.64		1.80	-3.0	-2.0
2.14		2.30	-3.0	-2.0
2.65		2.82	-3.0	-2.0
3.16		3.33	-3.0	-2.0
3.66		3.83	-3.0	-2.0
4.16		4.32	-3.0	-2.0
4.66		4.83	-3.0	-2.0
5.16		5.32	-3.0	-2.0
5.66		5.82	-3.0	-2.0
6.16		6.32	-3.0	-2.0
6.66		6.82	-3.0	-2.0
7.16		7.32	-3.0	-2.0
7.67		7.84	-3.0	-2.0
8.18		8.35	-3.0	-2.0
8.68		8.85	-3.0	-2.0
9.18		9.35	-3.0	-2.0
9.68		9.85	-3.0	-2.0
10.18		10.35	-3.0	-2.0
10.68		10.85	-3.0	-2.0
11.20		11.37	-3.0	-2.0
11.71		11.89	-3.0	-2.0
12.23		12.40	-3.0	-2.0
12.74		12.90	-3.0	-2.0
13.24		13.40	-3.0	-2.0
13.73		13.90	-3.0	-2.0
14.23		14.40	-3.0	-2.0
14.72		14.89	-3.0	-2.0
15.22		15.39	-3.0	-2.0
15.72		15.89	-3.0	-2.0
16.17		16.32	-3.0	-2.0
16.63		16.81	-3.0	-2.0
17.13		17.30	-3.0	-2.0
17.64		17.82	-3.0	-2.0
18.16		18.33	-3.0	-2.0
18.68		18.85	-3.0	-2.0
19.20		19.36	-3.0	-2.0
19.71		19.89	-3.0	-2.0
20.22		20.38	-3.0	-2.0
20.72		20.90	-3.0	-2.0
21.24		21.42	-3.0	-2.0
21.76		21.93	-3.0	-2.0
22.25		22.42	-3.0	-2.0
22.76		22.93	-3.0	-2.0

23.26	23.43	-3.0	-2.0
23.78	23.95	-3.0	-2.0
24.27	24.43	-3.0	-2.0
24.78	24.94	-3.0	-2.0
25.29	25.46	-3.0	-2.0
25.79	25.97	-3.0	-2.0
26.29	26.46	-3.0	-2.0
26.80	26.96	-3.0	-2.0
27.29	27.47	-3.0	-2.0
27.80	27.97	-3.0	-2.0
28.30	28.48	-3.0	-2.0
28.82	29.00	-3.0	-2.0
29.33	29.51	-3.0	-2.0
29.85	30.03	-3.0	-2.0
30.36	30.52	-3.0	-2.0
30.85	31.01	-3.0	-2.0
31.33	31.51	-3.0	-2.0
31.83	32.02	-3.0	-2.0
32.35	32.53	-3.0	-2.0
32.87	33.04	-3.0	-2.0
33.37	33.54	-3.0	-2.0
33.88	34.05	-3.0	-2.0
34.38	34.55	-3.0	-2.0
34.88	35.05	-3.0	-2.0
35.38	35.55	-3.0	-2.0
35.88	36.05	-3.0	-2.0
36.38	36.55	-3.0	-2.0
36.88	37.05	-3.0	-2.0
37.38	37.55	-3.0	-2.0
37.88	38.05	-3.0	-2.0
38.38	38.55	-3.0	-2.0
38.88	39.06	-3.0	-2.0
39.40	39.57	-3.0	-2.0
39.91	40.07	-3.0	-2.0
40.41	40.57	-3.0	-2.0
40.90	41.07	-3.0	-2.0